



LUCAS *Coatings & Mastics for the Roofing Trade*
R. M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

PRODUCT DATA BULLETIN

#201 FIBRATED FOUNDATION COATING

PURPOSE

Lucas #201 Fibrated Foundation Coating is a fast drying fiber reinforced asphalt coating intended for application to below-grade foundation walls. Fibrated coatings allow greater film thickness than non-fibrated coatings or hot mopped asphalt.

PRODUCT DESCRIPTION

Lucas #201 is manufactured from high softening point asphalts, petroleum solvents and reinforcing fibers. It is formulated in three seasonal grades for ease of application and is filtered for spray upon request.

APPLICATION

The surface to be coated must be clean and dry. Apply #201 at a rate of 3 gallons per 100 square feet with a brush, roller or suitable spray equipment. Additional coats may be applied to achieve the desired film thickness. If desired, seal form ties with Lucas #379 prior to coating the foundation with #201.

CAUTION

Combustible mixture; keep away from heat and open flame. Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. If swallowed, do not induce vomiting. Keep out of reach of children. Read MSDS prior to use.

California Proposition 65 Warning: This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

#201 SPECIFICATION

Applicable Specifications:	IRC 406.1, IBC 1801.2
Viscosity ASTM D-2823 (Summer Grade)	35 to 40 sec @ 77°F (25°C) (15,000 cps.)
Recommended rate of application	3 gal. Per 100 sq. ft.
% Asphalts	42 min
% Solids	46 min
% Non-volatile	70 max
Weight per gallon	7.5 lbs.
Flash Point (TCC)	+100°F (38.7°C)
Container Sizes	5, 55, Bulk

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.