



**LUCAS** *Coatings & Mastics for the Roofing Trade*  
R. M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

## **PRODUCT DATA BULLETIN**

### **#2115 SILANE/SILOXANE WATERPROOFING Water-Based**

#### **PURPOSE**

Lucas #2115 is a silane monomer / siloxane oligomer based waterproofing treatment intended for application to alkaline surfaces such as brick, mortar, concrete block, cultured stone, sandstone and concrete. #2115 is not intended for use on some types of non-silicate natural stone. Applications of #2110 will not change the appearance of masonry or concrete. #2115 is a higher performance version of our #2110 intended for horizontal surfaces.

#### **PRODUCT DESCRIPTION**

Lucas #2115 is manufactured from a blend of silanes and siloxanes specifically suited for waterproofing applications. Silane's small molecule size allows for effective penetration of higher density materials while siloxanes more effectively treat larger pores. Silanes react with moisture in an alkaline environment to form hydroxy groups that produce a hydrophobic water repellent surface. Siloxanes react with silica to produce hydrophobic crystalline structures. This product is supplied in a water vehicle.

#### **APPLICATION**

Mechanically mix before using. Do not store above 90°F. The surface must be clean but may be damp, although penetration will be lessened. Apply with a brush, long knap roller or an airless or garden type sprayer until the surface is fully saturated. Protect glass and landscaping from contact with this product. Lucas #2115 will permanently fuse to glass surfaces and cannot be removed.

#### **CAUTION**

Avoid prolonged contact with skin. If irritation occurs seek medical attention. If swallowed, do not induce vomiting. Keep out of reach of children. Read MSDS prior to use.

California Proposition 65 Warning: This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

## **#2115 SPECIFICATION**

<b>Applicable Specification</b>	<b>NA</b>
<b>Recommended rate of application</b>	<b>Fully saturate surface</b>
<b>%Reduction Weight Gain (21 day immersion)</b>	<b>91.3 %</b>
<b>Average Depth of Penetration</b>	<b>2 mm</b>
<b>Weight per gallon</b>	<b>8.5 lbs.</b>
<b>Flash Point (TCC)</b>	<b>None</b>
<b>Container Sizes</b>	<b>5, 55</b>

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.