



# **LUCAS** *Coatings & Mastics for the Roofing Trade*

R. M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

## **PRODUCT DATA BULLETIN**

### **#2500 ACRYLIC MASONRY CAULK/SEALANT**

#### **PURPOSE**

Lucas #2500 Acrylic Masonry Caulk/Sealant is an elastomeric caulk and sealant intended for sealing small cracks and penetrations in concrete and masonry walls prior to coating with Lucas #2000 Elastomeric Wall Coating. #2500 is also suitable for topical repairs to masonry walls.

#### **PRODUCT DESCRIPTION**

Lucas #2500 is formulated from 100% acrylic polymers. This is a water-based material and must be kept from freezing.

#### **APPLICATION**

Do not store above 90°F. Apply only at temperatures above 40°F and rising with less than 90% humidity and no threat of rain for 48 hours. Horizontal surfaces must be power-washed clean with a suitable residue-free detergent such as Lucas #115. The surface may be damp but must be free of standing water. Surface temperatures should be under 100°F to avoid premature curing.

This product displays very good resistance to intermittent ponding water. However, when applied to areas that retain water permanently or near-permanently, service life will be severely diminished and adhesion failure can be expected.

Apply with a quart size caulk gun, trowel or paintbrush. Knock down beads of caulk to 1/8 inch thickness with a paintbrush. Not intended for caulking large gaps. Large gaps should be grouted with mortar prior to sealing. Allow to dry before top coating. Clean up uncured coating with soap and water.

## CAUTION

Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. Keep out of reach of children. Read MSDS prior to use.

California Proposition 65 Warning: This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

### #2500 SPECIFICATION

Viscosity ASTM D-562	100,000+ cps @ 77°F (25°C)
Recommended rate of application	1/8 inch thick
% Elongation	200 min
% Solids	60 min
Weight per gallon	12 lbs.
Flash Point (TCC)	None
Container Sizes	10 oz. tube
Colors	White

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.