



LUCAS *Coatings & Mastics for the Roofing Trade*

R. M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

PRODUCT DATA BULLETIN

#7330 PAVER SEALER & SAND STABILIZER Water-Based - High Gloss

PURPOSE

Lucas #7330 Paver Sealer & Sand Stabilizer—Water Based is a VOC compliant water borne acrylic protective coating for concrete pavers. #7330 will penetrate the surface and bind the concrete together minimizing erosion of the surface while improving the color and appearance of the surface. As the product seals the paver surface, it will also penetrate and bind together the sand in the paver joints. This limits movement, retards the growth of weeds and inhibits insects such as ants that displace the joint sand.

PRODUCT DESCRIPTION

Lucas Paver Sealer is manufactured from durable, high Tg acrylic resin in a water vehicle. Formulated for maximum water blush resistance and a high gloss appearance.

APPLICATION

Do not apply to concrete pavers in temperatures over 80° F to avoid blistering or pin-holing. Material temperature must be 50°F minimum. Application temperature must be 50° F minimum. Not resistant to petroleum products or animal fats. Do not allow to freeze before application and for 24 hours after application.

Apply product as it comes from the container with a high volume commercial pump sprayer with a 1/2 gallon per minute tip or with a 3/4 inch nap roller. Do not use form oil sprayers as the oil will contaminate the sealer. Apply 150 sq. ft. per gallon.

CAUTION

Wear appropriate protective clothing including rubber gloves and safety goggles. If irritation occurs, flush with water and seek medical attention. If swallowed, do not induce vomiting. Keep out of reach of children. Read MSDS prior to use.

California Proposition 65 Warning: This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

#7330 SPECIFICATION

Specification	ASTM C-1315, Type I, Class A & B, ASTM C-309, Type I, Class A & B, AASHTO M-148, Type 1 & 1D, Class A & B
Viscosity	150 cps
Recommended rate of application	150 sq. ft. per gallon
% Solids	30 min
Weight per gallon	8.7 lbs.
Dry to touch	2 to 4 hours
Wheel traffic	12 hours
Flash point (TCC)	none
VOC	less than 25 g/l
Colors	Clear
Container sizes	1, 5, 55, 250 gal tote

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.